

## WDD 81V - Desoldering Station Set

Bestellnr.:0053256699



**Desoldering station diigital 95 W, 230 V compressed air or inert gas operated**

### Top Attributes

- 1 channel
- Digital controlled electronic for soldering or desoldering tools up to 80 W
- Compressed air converter provides vacuum for the desoldering iron
- Inlet pressure 500 - 600 KPA (58 - 87 psi) oilfree, dry compressed air or inert gas
- Temperature range 50°C - 450°C
- Calibration box WCB 2 (005 31 180 99) may be connected for CALIBRATION, LOCK OUT or OFFSET function
- Protection class 1
- Antistatic housing
- Equipotential bonding (normal state hard grounded)
- Automatic tool recognition
- Dimensions: 166 x 115 x 101 mm (W x L x H)
- For use with external compressed air

### Technical Data

Display technology	LED
Equipotential Bonding/ hard grounding explanation	Normal state
Temperatur control comment	Button
Display included & Size	Medium
Display information content	Medium
ESD safe	Yes
Equipotential Bonding/ hard grounding	Yes
Display backlight	No
Antistatic housing	Yes

Temperature stability	5 °C
Power unit wattage	95 W
Mains supply Voltage	230 V
Power supply frequency	50 Hz
Output voltage	24 V
Protection class Soldering iron	3
Protection class Control/ Power unit	1
Number of tools controlled simultaneously	1
Temperature accuracy	9 °C
Temperature regulation	50 - 550 °C

### Packaging information

Shelf pack size (Units per shelf pack)	1
--	---