



Materials and Finish

- Insulator: PBT with Glass Fiber, UL94V-0, Black
- Shell: Steel, Nickel Plated
- Contact: Copper Alloy, with 2-Gold Flash Plating over Nickel
- Watertight Frame: PBT with Glass Fiber, UL94V-0, Black
- O-Ring: Silicone
- Epoxy Sealant: Epoxy
- DEGREE OF PROTECTION: IP67 AS PER IEC60529

Mounting Option

4- BRACKET #4-40 UNC WITH BOARDLOCKS



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY.

Contact Information

40- RIGHT ANGLE TAIL, 10.3 [.406], STANDARD FOOTPRINT

Electrical Characteristics

- Current Rating: Signal Contact: 5.0 A
High Power Contact: 10.0 A - 14.0 A
- Dielectric Withstanding Voltage: 1000 V / 1 Min
- Insulation Resistance: 5000 Megohm Min.
- Signal Contact Resistance: 10 Milliohms Max.
- High Power Contact Resistance: 1.0 Milliohms
- Working Temperature: -55C to +105C

| | | | |
|---|--|-------------------------------------|-----------------|
| Power Combo Waterproof D-Sub Connector RECEPTACLE PART NUMBER: 630-W7W-240-014 | | ACAD REFERENCE NO. 628-W7W Assembly | |
| | | DRAWN: R.STA.MONICA | DATE: June.4/13 |
| | | CHECKED: | DATE: |
| | | SCALE: NTS | SHEET 1 OF 1 |
| | | DRAWING NUMBER 628-W7W Assembly | ISSUE 1 |



EDAC INC
TORONTO, ONTARIO
CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.