

PCT-1000 Programmable Preheater



More Heat, Lower Temperatures for Faster, Higher Quality Results

The new PCT-1000 is a programmable preheater that provides users exceptional ability to increase heat capacity with highly controlled thermal output. The preheater is ideal for aiding high thermal demand applications including lead-free, multi-layer boards and large ground planes. The PCT-1000 can be used in a variety of processes including soldering, desoldering, SMD rework operations and, with its added heat capacity, will provide faster production rates while lowering overall process temperatures.

Programmable Controls

With four programmable heating zones and one cooling zone, users select time and temperature targets, creating a preheat thermal profile.

The PCT-1000 features an advanced heat control function where the temperature is controlled either at the

heater output (internal) or at the board (external). The “external” control function uses a thermocouple which can be placed on the board or a component. The external control function enables users to heat with high levels of assurance; preventing such undesirable effects as underside component reflow, thermal shock to sensitive components and damaging peak temperatures.

The PCT-1000 Powerful Heating Improves Productivity

PCT-1000 is equipped with the highly advanced heater design found on sophisticated OK International rework systems. Its convection heater creates a vortex effect that efficiently directs and concentrates heat. This, coupled with the precise feedback control and thermal profiling capability, establish the PCT-1000 as a powerful, precise benchtop solution for increasing productivity.



Four-zone thermal profiling with independent time and temperature control.



User selects internal or external control.

OKinternational

OKi
www.okinternational.com

PCT-1000 Programmable Preheater

Easy Operation and Profile Storage

The PCT-1000 is easy-to-use with clearly marked controls. The front panel features a 20 X 4 LCD display and 3 input buttons. Step by step programming makes profile creation simple and straight forward. The system stores up to 10 thermal profiles plus one default start up profile.

Unique, Flexible Board Holders

While the PCT-1000 can be used with or without a board holder, users often need a quick and flexible way to position a board over the preheater.

The new BH-1000 board holder consists of posts and rails and is a highly flexible system. It has two sets of post-rail assemblies (two posts, one rail per assembly). Two sliding clips are mounted on each rail and require minimal board-edge space to clamp the board. The post-rail assemblies can be located as close as 12 mm (1/2") to virtually any distance apart. Additionally, each post-rail system can be converted to a stand-alone post-pin configuration with removal of the rails and by adding the threaded pins (shown right). The pins can be used for holding board tooling holes or for board support.



2 options: post-rail system (above) or post-pin systems (below)



PCT-1000 with foot switch



PCT-1000 External Type K thermocouple inputs

Key Features & Benefits

- Adds heat capacity and enables lower process temperatures
- Increases through-put and reliability of soldering, desoldering and SMD rework processes
- Four-zone programmable settings for time and temperature to create optimum thermal profiles for varying application demands
- Storage for up to fifty users defined profiles for quick, easy set-up
- User selectable control of heating at source (internal) or at target (external)
- Controlled cool-down eliminates thermal shock to PCB and components
- System safety feature automatically shuts off heating when fan is stopped
- High efficiency vortex heater design maximizes ramp to temperature for increased productivity

PCT-1000 Programmable Preheater Specifications

Power Consumption	350 W
Rated Power	1200 W
Input	100-240 VAC, 50/60 Hz
Temperature Range	50° to 350° C
Temperature Control	Type K Thermocouple feedback with users selectable source (internal) or target (external) control External: includes two Type K inputs
Air Flow	Fixed at 19cfm (538 l/minute)
Programs	Storage for fifty (50) thermal profiles
Approvals	CE, cTUVus
Maximum time per zone	300 seconds

Part Number

PCT-1000

Description

Programmable Preheater, 350W convection; Type-K T/C kit, foot switch, power cord, User Manual, Advanced User Guide

PCT-FS1

PCT-1000 Foot switch

BH-1000

Post-Rail Board Holder system; four posts, two rails with sliding clips, four support pins, flat-head support (screw)

BH-SP1000

Single Post Board Support; post with height adjustment, four support pins

BH-PK1000

Support Pin Kit; four support pins, flat-head support screw

BH-RK1000

Board Holder Rail Kit; two 300mm rails, four support pins