

## Accessories - ICC-MT 1,5-2,5 - 3190580

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Module male contact, is inserted into the ICC connector shell after the conductor has been crimped, for conductors from 1.5-2.5 mm<sup>2</sup>



### Key commercial data

Packing unit	1
Minimum order quantity	100
Catalog page	Page 851 (CC-2011)
GTIN	 4 017918 093419
Custom tariff number	85389099
Country of origin	GERMANY

### Technical data

#### Technical data

Nominal current	12 A
Conductor cross section stranded min.	1.5 mm <sup>2</sup>
Max. conductor cross section, stranded	2.5 mm <sup>2</sup>

#### Connection data

Core diameter including insulation	2.11 mm ... 3.1 mm
Stripping length of individual wires	4 mm

### Classifications

#### eclass

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402

# Accessories - ICC-MT 1,5-2,5 - 3190580

## Classifications

etim

ETIM 3.0	EC001121
ETIM 4.0	EC001121

unspsc

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121410
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

---

Approval details



## Drawings

Dimensioned drawing

