



RUE SAINT-HENRI 11, P.O. BOX 834 - CH-2800 DELÉMONT / SWITZERLAND

## Your selected product

### Jumpers - Male Jumpers

Series 999

**999-11-112-10**

2.54 mm, Male Jumpers

Available with or without insulator, and with 2.54, 5.08 or 7.62 mm pin spacing. For use with standard socket connectors.

#### Technical specs.:

**Insulator:** Black glass filled polyester PBT-GF30-FR

**Flammability:** UL 94V-O

**Contact:** Brass CuZn36Pb3 (C36000)


**Connecting pin Ø:** 0.56 mm

**Mechanical life:** Min. 100 cycles

**Rated current:** 3 A

**Contact resistance:** Max. 10 mΩ

**Dielectric strength:** Min. 1000 V RMS



## Ordering information RoHS-compliant parts

### P Plating code

1 Gold 0.25 µm

### Option

Jumpers without insulator with wire Ø 0.50 mm instead of 0.56 mm. Part numbers:

B = 2.54 mm 999-51-110-10

B = 5.08 mm 999-51-112-10

B = 7.62 mm 999-51-113-10

[General technical specs](#). [View CAD](#)

### Advanced information:

|                      |                            |  |
|----------------------|----------------------------|--|
| Order Codes          |                            |  |
| <b>999-11-112-10</b> | <a href="#">View Image</a> |  |

---

### 999-11-112-10

Jumpers for socket connectors,  
B = 5.08 mm, not insulated

---