



- SPECIFICATIONS:
- CURRENT RATING: AC: 100V 1A  
DC: 24V 2A
  - CONTACT RESISTANCE: 20mΩ MAX.
  - INSULATION RESISTANCE: DC 500V 100MΩ MIN.
  - VOLTAGE WITHSTANDING: AC 500V 1 MINUTE
  - INSERTION FORCE: 4Kg MAX.
  - WITHDRAWAL FORCE: 1kg MIN.
  - LIFE TEST: 5,000 CYCLES MIN. AFTER TESTING,
  - CONTACT RESISTANCE SHALL NOT EXCEED 100mΩ
  - UNLESS OTHERWISE SPECIFIED TOLERANCE ARE: ±0.2

|     |                  |     |   |
|-----|------------------|-----|---|
| 4   | CONTACT TERMINAL | 5   | BRASS 0.7t<br>SILVER PLATING            |
| 3   | PLATE            | 1   | BAKELITE BOARD 1.4t                     |
| 2   | EARTH TERMINAL   | 1   | PHOSPHOR BRONZE 0.25t<br>SILVER PLATING |
| 1   | BODY             | 1   | PBT UL 94V-0<br>BLACK COLOR             |
| LTR | PART NAME        | QTY | MATERIAL & SPEC                         |


 Singatron Enterprise Co., Ltd.  
 信音企業股份有限公司

TITLE 5P 180° DIN CONNECTOR

|       |            |         |                      |
|-------|------------|---------|----------------------|
| DWN   | UNIT: MM   | CAD NO. | DJ-006               |
| CHKD  | SCALE: 2/1 | DWG NO. | NEW NO. 2DU-00600003 |
| APPVD | SIZE: B4   | APP NO. | OLD NO. DJ-006       |