

**Industrial Ethernet  
IE-PS-V04P-2LC-MM-BP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



PushPull plug-in connector set according to IEC  
61076-3-106 ver.4 (IEC24702), plastic with LC insert

**General ordering data**

|            |   |
|------------|---|
| Type       | IE-PS-V04P-2LC-MM-BP  |
| Order No.  | <a href="#">1963330000</a>  |
| Version    | FO connector, Variant 4, LC-Duplex multi-mode,<br>with kink prevention, IP 67 |
| GTIN (EAN) | 4032248651801   |
| Qty.       | 10 pc(s).   |

**Data sheet**

**Industrial Ethernet  
IE-PS-V04P-2LC-MM-BP**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Net weight 43.3 g

**Temperatures**

Operating temperature -40 °C...70 °C      Storage temperature  
 Installation temperature

**Downloads**

GOST Approval      POCC  
 DE.ME25.B01411.pdf

**General data**

|                       |                                     |                           |   |
|-----------------------|-------------------------------------|---------------------------|---|
| Colour                | Miscellaneous                       | Connection 1              | LC  |
| Connection 2          | LC                                  | Description of article    | Variant 4, LC-Duplex multi-mode, with kink prevention |
| Fibre type            | Multimode                           | Housing main material     | PA UL 94 V0   |
| Insertion loss        | 0.5 dB singlemode, 0.4 dB multimode | Plugging cycles           | 500   |
| Protection degree     | IP 67                               | Return loss (attenuation) | 40 dB singlemode; 30 dB multimode                     |
| Sheath diameter, max. | 10 mm                               | Sheath diameter, min.     | 5 mm  |

**Standards**

Connector standard      IEC 61076-3-106 Var. 4,  
 IEC 61754-20

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC001121    | ETIM 4.0   | EC002641    |
| ETIM 5.0   | EC002641    | ETIM 6.0   | EC002641    |
| UNSPSC     | 30-21-18-10 | eClass 5.1 | 27-26-07-08 |
| eClass 6.2 | 27-26-07-08 | eClass 7.1 | 27-25-05-04 |

**Approvals**

Approvals



ROHS      Conform

**Data sheet**

**Industrial Ethernet  
IE-PS-V04P-2LC-MM-BP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Dimensioned drawing**

