



General ordering data

Order No.	9507990000
Part designation	NexT 74/55/20 4gp 7032
Version	Ex enclosure, 205 mm, 740 mm, 550 mm, Sheet steel 2.02 mm (14 SWG)
EAN	4008190499556
Qty.	1 pc(s).

Dimensions

Fixing dimension, height	540 mm
Fixing dimension, width	606 mm
Height	205 mm
Length	740 mm
Width	550 mm

General details

Cover fixing	Removable cover + M6 screws
Enclosure fixing	Outside mounting with 10 mm holes
Integral fixing	4 x 10 mm spacers
Sealing material	Chloroprene (cover & flange)
Version cover	closed
Colour	RAL 7032 - pebble grey
Surface finish	RAL 7032, textured
Class of protection to EN 60529	IP 66
Weight	23,500 g
Ambient temperature, min.	-40 °C
Ambient temperature, max.	85 °C

Screwed cable glands top/bottom

M 12	141
M 16	103
M 20	64
M 25	39
M 32	20
M 40	16

Screwed cable glands top/bottom

M 50	6
M 63	5
M 75	4
Side of enclosure	Top / Bottom

Screwed cable glands, left/right

M12	141
M16	103
M20	64
M25	39
M32	20
M40	16
M50	6
M63	5
M75	4
On housing side	left / right

Approvals

Approvals institutes

**Classifications**

ETIM 2.0	EC000049
ETIM 3.0	EC000049
eClass 4.1	27-14-12-06
eClass 5.0	27-18-05-02
eClass 5.1	27-18-05-02

Similar products

Order No.	Part designation	Version
9523700000	NexT 74/55/20 0gp 7032	Ex enclosure, 205 mm, 740 mm, 550 mm, Sheet steel 2.02 mm (14 SWG)
9523560000	NexT 74/55/20 0gp ss	Ex enclosure, 205 mm, 740 mm, 550 mm, Stainless steel 1.4404
9523000000	NexT 74/55/20 1gp 7032	Ex enclosure, 205 mm, 740 mm, 550 mm, Sheet steel 2.02 mm (14 SWG)
9522720000	NexT 74/55/20 1gp ss	Ex enclosure, 205 mm, 740 mm, 550 mm, Stainless steel 1.4404
9507920000	NexT 74/55/20 2gp 7032	Ex enclosure, 205 mm, 740 mm, 550 mm, Sheet steel 2.02 mm (14 SWG)
9508730000	NexT 74/55/20 2gp ss	Ex enclosure, 205 mm, 740 mm, 550 mm, Stainless steel 1.4404
9522860000	NexT 74/55/20 3gp ss	Ex enclosure, 205 mm, 740 mm, 550 mm, Stainless steel 1.4404
9508800000	NexT 74/55/20 4gp ss	Ex enclosure, 205 mm, 740 mm, 550 mm, Stainless steel 1.4404