



NOTES:

- 1.Using Temperature Range:  
-40°C~+120°C
- 2.RoHS Compliance
- 3.Height: TS-35N: 35.3mm  
TS-35/15N: 42.8mm
- 4.Screw Torque Value: 0.4N •m(MAX)

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

2	SCREW	STEEL	M3/Zn Plated
1	HOUSING	PA66	UL94-V0 GREY
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	LJY	DATE	2020.11.27	UNITS	MM	SHEET/OF	1 / 1
CHK.	Lj.Liang	DATE	2020.11.27	SCALE	3:1 ( : )		
APP.	Webb.Liu	DATE	2020.11.27	NAME	SS2-B33848		
<b>DINKLE</b> DINKLE ENTERPRISE CO., LTD.				DWG NO.	SP-03-SS2B33848		

REV.	CONTENT	NAME	DATE
△			